

A photograph of a fireplace with a black Supreme door. The fireplace is set into a stone wall. To the left of the fireplace is a stack of logs. In the foreground, a glass of wine is visible. The door is open, showing a fire burning inside. The text "Stock Size" is overlaid on the image in a white box.

Stock Size

Supreme Air Tight Fireplace Doors

Stock size Supreme door with standard black finish, wooden block handles and optional swing style screen

Gain control of your fire


Each door features a continuous woven gasket that seals them to the door frame. The combination of these gaskets with a positive locking latch virtually eliminates cold drafts, heat loss and odor from coming through the fireplace opening.

Designed for maximum sealing quality

The Supreme is ideal for closed door heating fireplaces and to solve problems with troublesome applications.

WILKENING
Fireplace

Standard features



Room Air Inlet



Black Spring
Handle

or



Stained Wooden
Block Handle



2" Mounting
Flange



Tempered or
Ceramic Glass

Fire screen options



Sliding Fire Screen
(Standard feature)



Swinging Fire Screen
(Optional)

SPECIFICATIONS					
Model number	Outer diameter frame size	Fits opening widths of	Fits opening heights of	Glass size	Mounting flange outside dimension
37260	37" w x 26" h	30½" - 35"	23" - 25½"	14" w x 19½" h	30½" w x 22¾" h
37285	37" w x 28½" h	30½" - 35"	25½" - 28"	14" w x 22" h	30½" w x 25¼" h
41260	41" w x 26" h	35" - 39"	23" - 25½"	16" w x 19½" h	34½" w x 22¾" h
41285	41" w x 28½" h	35" - 39"	25½" - 28"	16" w x 22" h	34½" w x 25¼" h
41310	41" w x 31" h	35" - 39"	28" - 30½"	16" w x 24½" h	34½" w x 27¾" h
45285	45" w x 28½" h	39" - 43"	25½" - 28"	18" w x 22" h	38½" w x 25¼" h
45310	45" w x 31" h	39" - 43"	28" - 30½"	18" w x 24½" h	38½" w x 27¾" h

Tested to UL 907 and listed with Intertek testing when ordered with ceramic glass and wood handles



Manufactured by:



9608 State 371 N.W.
Walker, MN 56484

Your dealer is: